SLATEFIBER

PS 165 SF

Product sheet

The $6^{1/2}$ " (16.5cm) 2-way separate Slatefiber kit can be summed up in one word: efficient. This product incorporates the essence of Focal's latest technologies to deliver performance, reliability and French manufacturing. With standard dimensions and a smart design, it can be installed in most vehicles on the market without the need for an additional dedicated amplifier. However, you can still link these speaker

drivers to an amplifier if you want to get the very best performance out of them.



Key points

- Made in France in the Focal workshops
- High power handling for intensive use
- Little amplification requirements due to high sensitivity
- Tough design and high quality materials
- Flexible installation options

Woofer 165mm Depth 70mm Cone Slatefiber Maximum power 160W Nominal power 80W RMS Sensitivity (2.83V/1m) 91dB Frequency response 60Hz - 21kHz Impedance 4 Ω Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Туре	2-way component kit
Cone Slatefiber Maximum power 160W Nominal power 80W RMS Sensitivity (2.83V/1m) 91dB Frequency response 60Hz - 21kHz Impedance 4 Ω Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Woofer	165mm
Maximum power 160W Nominal power 80W RMS Sensitivity (2.83V/1m) 91dB Frequency response 60Hz - 21kHz Impedance 4 Ω Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Depth	70mm
Nominal power 80W RMS Sensitivity (2.83V/1m) 91dB Frequency response 60Hz - 21kHz Impedance 4 Ω Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Cone	Slatefiber
Sensitivity (2.83V/1m) 91dB Frequency response 60Hz - 21kHz Impedance 4 Ω Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Maximum power	160W
	Nominal power	80W RMS
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Sensitivity (2.83V/1m)	91dB
Voice-coil diameter 25mm Magnet Ferrite Suspension Butyl Tweeter Aluminium/Magnesium	Frequency response	60Hz - 21kHz
Magnet Ferrite Suspension Butyl Aluminium/Magnesium	Impedance	4 Ω
Suspension Butyl Tweeter Aluminium/Magnesium	Voice-coil diameter	25mm
Tweeter Aluminium/Magnesium	Magnet	Ferrite
Tweeter	Suspension	Butyl
inverted dome tweeter	Tweeter	Aluminium/Magnesium inverted dome tweeter
Crossover Independent woofer/tweeter crossovers	Crossover	•



MADE IN